

## **Liquid Receiver Fact Sheet - Vertical**

Temprite's line of Liquid Recievers includes Vertical Liquid Receivers for small- to large-refrigerant systems. A Liquid Receiver is a storage tank for holding liquid refrigerant and is located after the condenser in a refrigeration system. A Liquid Receiver is an important part of any system because it ensures liquid refrigerant is entering the

expansion device. Each Receiver has Inlet and Outlet connections and a threaded port for installation of an overpressure safety relief device.

Temprite Liquid Receivers accommodate all refrigerants: carbon dioxide (CO<sub>2</sub>), ammonia (NH<sub>3</sub>), and hydrocarbons (HCs), including ethane, isobutane, and propane.


The smallest vertical reciever, Model VR6-12, has a mounting stud. Fixed mounting feet are installed on Models VR8-16 through VR18-60. Models VR14-36 through VR18-60 also have lifting lugs on their top domes. (See graphic below.) Horizontal receivers are also available. All receivers are welded and have all-steel components.


Custom Liquid Receivers and options such as sight glasses and sensors are available for all models.

Maximum Working Pressure: 44.8 bar (650 PSI) VR6-12; All other sizes: 41.4 bar (600 PSI)				
	Pump Down Capacity			
Model	R22	R410A	R134a	R404A
VR6-12	4.9 kg	4.3 kg	5.0 kg	4.3 kg
	10.8 lb	9.5 lb	11.0 lb	9.4 lb
VR8-16	11.7 kg	10.4 kg	11.9 kg	10.3 kg
	25.9 lb.	22.8 lb	26.3 lb	22.6 lb
VR10-20	23.7 kg	20.9 kg	24.0 kg	20.6 kg
	52.3 lb	46.1 lb	53.0 lb	45.5 lb
VR12-24	41.2 kg	36.3 kg	41.8 kg	35.9 kg
	90.8 lb	80.0 lb	92.2 lb	79.1 lb
VR14-36	75.3 kg	66.4 kg	76.5 kg	65.6 kg
	166.1 lb	146.4 lb	168.6 lb	144.6 lb
VR16-48	141.1 kg	124.3 kg	143.2 kg	122.8 kg
	311.0 lb	274.1 lb	315.6 lb	270.7 lb
VR18-60	217.2 kg	191.4 kg	220.4 kg	189.1 kg
	478.8 lb	421.9 lb	485.8 lb	416.8 lb

All pump down capacities are calculated using 90% of receiver volume at 90° F.

For more information, Contact temprite@temprite.com or call I.800.552.9300; outside the U.S.: 630.293,5910. Fax: 630.293.9594. Website: www.temprite.com







MODELS VR14-36 - VR18-60

For translations of this fact sheet, go to our website or scan the QR code.

go to our website or scarrine Qir code.